

BriskHeat® Plugs for Composite Heat Curing Blankets

Description	Image	NEMA	Voltage	Amps	Ground	Approval	Plug Part Number	Blanket Plug Part Number Suffix
Bare Wires		N/A	N/A	N/A	N/A		N/A	A
Twist Lock 3 Pole 3 Wire Delta		N/A	125/250	30A	No	UL	10108	B
Twist Lock 3 Pole 4 Wire		L14-30	250	30A	Yes	UL SA	11270	C
Straight Blade 2 Pole 3 Wire		5-15	125	15A	Yes	UL SA	10113	D
Straight Blade 2 Pole 3 Wire		6-15	250	15A	Yes	UL SA	10478	E
Twist Lock 2 Pole 3 Wire		L5-30	125	30A	Yes	UL SA	40712	F
Twist Lock 2 Pole 3 Wire		L6-30	250	30A	Yes	UL SA	10814	G
3 Pole CPC (Circular Plastic Connector)		N/A	250	30A	Yes		20937-01	H
Hazardous Area Raintight Turn and Pull (4 pin)		N/A	480	30A	Yes	Class I Division 1 & 2, Groups D*	41024-02	I
Hazardous Area Raintight Turn and Pull (3 pin)		N/A	480	30A	Yes	Class I Division 1 & 2, Groups D*	11008-01	J

* Suitable for hazardous areas due to the presence of gasoline or other gases or vapors of equivalent hazard (comparable to N.E.C. Class I, Group D), where construction and test procedures are required to meet applicable sections of MIL-E-5272C and MIL-E-4970A