


Heavy Duty Silicone Rubber Drum and Pail Heaters

Product Highlights

- ✓ Excellent solution for a wide range of poly and metal drum applications
- ✓ Extra-wide 4" (102mm) heater coverage
- ✓ Extra-long service life: Excellent durability and flexibility
- ✓ Grounded heating element meets NEC 427.23
- ✓ Easy adjustable thermostat control (°F or °C)
- ✓ **CE RoHS** Compliant 
- ✓ **SP** (NEW! see ordering options for details)

**Extra-Wide
Extra-Strong
Easier-to-Use**



Short Video

Specifications:

- Heating element is laminated between **two or three extra-thick layers** of 20 mil fiberglass reinforced silicone rubber
- Patented 360° grounded multi-stranded heating element is uniformly placed to maximize heat distribution
- Adjustable thermostat*
 - 50-425°F (10-218°C) for metal
 - 50-160°F (10-71°C) for plastic
- Moisture and chemical resistant
- Choice of voltage: 120VAC or 240VAC
- 450°F (232°C) maximum exposure temperature on heating surface
- Dielectric strength of over 2000 volts
- Power cord 6-foot (1.8m) long
- Spring closure can be expanded 3" (76mm)

Ordering Information:

- **Standard Heavy Duty (DHCS and DPCS series):** Designed with two extra-thick layers of fiberglass reinforced silicone rubber for excellent strength and durability.
- **Extra Heavy Duty (DHCH and DPCH series):** Longest lasting and most durable drum heater. Designed with three extra-thick layers of fiberglass reinforced silicone rubber for **ultimate strength and durability**.

Standard Sizes

Gallon (Liter) Size	Diameter in (mm)	Length in (mm)	Width in (mm)
5 (19)	11.1 (282)	35.0 (889)	4 (102)
15 (57)	14.0 (355)	44.0 (1118)	4 (102)
30 (114)	18.6 (473)	58.5 (1496)	4 (102)
55 (208)	22.3 (565)	70.0 (1778)	4 (102)

For Metal Drums/Pails

Gallon (Liter) Size	Watts	Std. Heavy Duty	
		120VAC	240VAC
5 (19)	550	DHCS10	DHCS20
15 (57)	700	DHCS11	DHCS21
30 (114)	1000	DHCS13	DHCS23
55 (208)	1200	DHCS15	DHCS25

Extra Heavy Duty	
120VAC	240VAC
DHCH10	DHCH20
DHCH11	DHCH21
DHCH13	DHCH23
DHCH15	DHCH25

For Poly (Non-Metal) Drums/Pails

Gallon (Liter) Size	Watts	Std. Heavy Duty	
		120VAC	240VAC
5 (19)	150	DPCS10	DPCS20
15 (57)	200	DPCS11	DPCS21
30 (114)	250	DPCS13	DPCS23
55 (208)	300	DPCS15	DPCS25

Extra Heavy Duty	
120VAC	240VAC
DPCH10	DPCH20
DPCH11	DPCH21
DPCH13	DPCH23
DPCH15	DPCH25

120VAC models are provided with a standard 3-prong NEMA 5-15 plug. 240VAC models come with bare wire connections.

Ordering Options:

- A. **Celsius Label Option:** Add a "-C" at the end of the part number.
- B. **NEW CSA Approved Option:** Add an "A" at the end of the part number. Includes bare wire leads.
- C. **Drum Heater without controlling thermostat:** Replace "C" with "N" in part number. External control is required with this option.

* If precise temperature control is required for your application, please contact BriskHeat or your local distributor for application assistance and product solutions.