

ACR® 4 ACCESSORIES

Type-J thermocouples and adaptors

Part No.	Description
11510	5 pack Type-J thermocouples rated to 425°F (218°C), 6 ft (1.8 m) 30 gage with mini connectors
11510-02	5 pack Type-J thermocouples rated to 900°F (482°C), 6 ft (1.8 m) 30 gage with mini connectors
11512-02	5 pack Type-J thermocouples rated to 500°F (260°C), 6 ft (1.8 m) 24 gage with standard male connectors
11512-03	5 pack Type-J thermocouples rated to 1300°F (704°C), 6 ft (1.8 m) 20 gage with standard connectors
41253	Thermocouple adaptor, std female to mini male



Thermocouple box and cable

Part No.	Description
11514-20	Modular Flat Cable, Plug to Plug 8p8c (RJ45, Ethernet), 15 ft (4.57 m) Unshielded
41247-122	ACR® 4 Thermocouple Box Assembly, Calibrated without Cable



Vacuum hose

Part No.	Description
20938	Replacement vacuum hose; 10 ft (3 m)



Vacuum bag feed-through

Part No.	Description
20931-01	Replacement vacuum bag feed-through



Printer paper

Part No.	Description
41247-149	Replacement thermal printer paper, 80 ft (24 m)



Input power cords

Part No.	Description
20937-124	10 ft (3 m) with Twist Lock Connector, 2P 3W, 125V/30A, NEMA# L5-30P Grounding
20937-125	10 ft (3 m) with Twist Lock Connector, 2P 3W, 125V/15A, NEMA# 5-15P Grounding
20937-224	10 ft (3 m), with Twist Lock Connector, 2P 3W, 240V/30A, 3P+E+N Grounding per IEC 60309
20937-244	10 ft (3 m) with Twist Lock Connector, 2P 3W, 240V/30A, NEMA# L6-30P Grounding

Output power cords

Part No.	Description
20936-40	4 Prong 120/240 VAC, 5 ft (1.52 m) 10/4 SJOOW with L15-30 Receptacle

Calibration Services & Plans for ACR® 4 Hot Bonders

Calibration Service

Part No.	Description
ACR4CALD	Calibration service for ACR® 4 hot bonder. Recommended to be done annually

3-Year Calibration Plan

Part No.	Description
ACR4CALD3-2	3-year calibration plan for ACR® 4 hot bonder

