

**CUSTOM TAPE DESIGN CHECKLIST**

Customer: \_\_\_\_\_ Submitted By: \_\_\_\_\_

Contact Name: \_\_\_\_\_

Phone: \_\_\_\_\_ Fax: \_\_\_\_\_

Application: \_\_\_\_\_

**TAPE SPECIFICATIONS:**

Environment:            Indoor            Outdoor            Wet-area            Hazardous (explain below)

Will tape be used on an electrically conductive surface?            Yes            No

Will tape be removed and reused?            Yes            No

Tape Insulation:            Standard            Heavy

Outside Material:            Fiberglass            Samox            Silicone

Maximum Application Temperature: \_\_\_\_\_ °F            °C

Dimensions:            Width: \_\_\_\_\_ Length: \_\_\_\_\_ inches            mm

Voltage Requirements:            120V            240V            480V            Other: \_\_\_\_\_            Grounded            Ungrounded

Lead Same End            Lead Opposite End

Connection Type:            Bare Wires            Crimped Ferrules            Separable 2-prong plug            Other: \_\_\_\_\_

Wattage Requirements (Special): \_\_\_\_\_ Per Square Inch            or            \_\_\_\_\_ Total Watts

Who will supply the Temperature Control:            Customer            BriskHeat (see Controller Checklist)

Built-in control options:            Adjustable up to 160°            Adjustable up to 425°            Time percent (TPO)

Single point thermostat \_\_\_\_\_ °F

**Special Instructions:**