

XTREMEFLEX® HEAVY INSULATED CLOTH HEATING TAPES

Specifications and Selection Guide

Series	Type	Maximum Exposure Temperature	Construction	Watt Density watts/in ² (watts/cm ²)	IP Rating	Lead Length ft (m)	Plug Type	Page
B00	Non-grounded	Single Install: Up to 932°F (500°C) Removable/Reusable: Up to 572°F (300°C)	Fiberglass	8.6 (1.3)	IP50	2 (0.6)	120 VAC: Separable 2-prong plug 240 VAC: Bare wire or crimped ferrule leads	72
BW0	Non-grounded	Single Install: Up to 932°F (500°C) Removable/Reusable: Up to 572°F (300°C)	Samox	13.1 (2.0)	IP50	2 (0.6)	120 VAC: Separable 2-prong plug 240 VAC: Bare wire or crimped ferrule leads	72
BIH	Non-grounded	Single Install: Up to 932°F (500°C) Removable/Reusable: Up to 572°F (300°C)	Fiberglass	Standard: 8.6 (1.3) Wide †: 5.1 (0.8)	IP50	2 (0.6)	120 VAC: Separable 2-prong plug 240 VAC: Bare wire or crimped ferrule leads	73
BWH	Non-grounded, high-watt density	Single Install: Up to 932°F (500°C) Removable/Reusable: Up to 572°F (300°C)	Samox	Standard: 13.1 (2.0) Wide †: 5.1 (0.8)	IP50	2 (0.6)	120 VAC: Separable 2-prong plug 240 VAC: Bare wire or crimped ferrule leads	73
BIH-G	Grounded	Up to 482°F (250°C)	Fiberglass	9.6 (1.5)	IP50	2 (0.6)	Bare wire leads	73
BWH-D	Dual element – increased flexibility	Single Install: Up to 932°F (500°C) Removable/Reusable: Up to 572°F (300°C)	Samox	13.1 (2.0)	IP50	2 (0.6)	120 VAC: 2-prong plug (NEMA1-15P) 240 VAC: Bare wire leads	74

† 1.75 in (44 mm) wide tape or greater



All Heavy Insulated Cloth Heating Tapes

Custom Sizes and Designs Available: Contact BriskHeat® or your local distributor for more information.

EASY WAYS TO ORDER

1. Contact your local distributor. Check BriskHeat.com to locate a local distributor.
2. Call BriskHeat® at 800-848-7673 or 614-294-3376. We have a staff of application specialists to solve your unique needs.
3. Order online at BriskHeat.com - 24/7.

PAYMENT TERMS

Credit Card Options



Net 30 Option

Net 30 Terms are available to qualified companies. Please contact your Account Manager for additional details.