

TSO Portable Bulb and Capillary Temperature Controller

Product Highlights

- ✓ Portable, plug-and-play design
- ✓ For indoor general purpose applications
- ✓ Manually set your desired temperature
- ✓ Bulb and capillary control
- ✓ Two temperature range choices to fit your application



Specifications:

- 120 or 240VAC
- Differential 6°F (3°C)
- Average accuracy of ±5°F (3°C)
- Maximum controller exposure temperatures: -40 to 160°F (-40 to 71°C)
- Copper bulb and capillary, 4 feet (1.2m) long
- Input power cord 6 feet (1.8m) long with standard plug
 - 120VAC: NEMA 5-15
 - 240VAC: NEMA 6-15
- Output receptacle:
 - 120VAC: NEMA 5-15R
 - 240VAC: NEMA 6-15R



Bulb Dimension

Diameter		Length	
Inches	mm	Inches	mm
3/8	10	4	102

Ordering Information:

Part number	Volts	Amps	Range
TS0991-250	120	15	60 to 250°F (16 to 121°C)
TS0991-550	120	15	150 to 550°F (66 to 288°C)
TS0992-250	240	15	60 to 250°F (16 to 121°C)
TS0992-550	240	15	150 to 550°F (66 to 288°C)

