

CUSTOM TAPE DESIGN CHECKLIST

Customer: _____ Submitted By: _____

Contact Name: _____

Phone: _____ Fax: _____

Application:

TAPE SPECIFICATIONS:

Environment:	Indoor	Outdoor	Wet-area	Hazardous (explain below)
--------------	--------	---------	----------	---------------------------

Will tape be used on an electrically conductive surface?	Yes	No
--	-----	----

	Yes	No
Will tape be removed and reused?	<input type="checkbox"/>	<input checked="" type="checkbox"/>

Tape Insulation: Standard Heavy

Outside Material: Fiberglass Samox

Maximum Application Temperature: °F °C

Dimensions: Width: Length: inches mm

Voltage Requirements:	120V	240V	480V	Grounded	Ungrounded
-----------------------	------	------	------	----------	------------

Lead Same End Lead Opposite End

Connection Type: Bare Wires Separable 2-prong plug Other:

Wattage Requirements (Special):	Per Square Inch	or	Total Watts
---------------------------------	-----------------	----	-------------

Who will supply the Temperature Control: Customer BriskHeat (see Controller Checklist)

Built-in control options: Adjustable up to 160° Adjustable up to 425° Time percent (TPO)

Single point thermostat °F

Special Instructions: