

END OF CIRCUIT LED MONITOR LIGHT KIT

- ▶ Super bright green LED light with 360° visibility
- ▶ Dual voltage use up to 240 VAC
- ▶ Approved for ordinary and hazardous area use
- ▶ For use with all BriskHeat self-regulating heating cables
- ▶ Pipe mounting using stainless steel pipe strap
- ▶ Surface mounting using built-in flanges
- ▶ Easy re-entry for maintenance
- ▶ Compatible with up to 4 in (102 mm) of insulation and cladding
- ▶ Hot work permit not required for installation

Specifications:

- **Maximum Voltage:** 110-240 VAC
- **Maximum Current:** 32 A
- **Minimum Installation Temperature:** -40°F (-40°C)
- **Minimum Ambient Temperature:** -40°F (-40°C)
- **Maximum Ambient Temperature:** 149°F (65°C)
- **Ingress Protection:** IP66/NEMA 4x
- **Lumen Output:** 10 Lumens
- **Construction:** Non-conductive FRP plastic body
- **Overall Height:** 8.2 in (208 mm)



Ordinary Locations
Hazardous Locations
Class I, Division 2, Groups A, B, C, D
Class II, Division 2, Groups F, G
Class III, Division 2

Ordering Information:

Part No.	Description
JHE-LG-GET	End of circuit monitor light kit. Green LED, Includes 6 in (152 mm) pipe strap and adapter for small diameter pipe installations. Cold-applied materials do not require heat gun, torch, or hot work permit for installation.

