

## ATEX WRAPAROUND TOTE TANK/IBC HEATERS

**NEW!**

### Features & Benefits

- ▶ ATEX approved
- ▶ Fully insulated design maximizes efficiency
- ▶ Temperatures up to 392 °F (200 °C)
- ▶ Robust construction for indoor or outdoor use — IP65
- ▶ Grounded for increased safety
- ▶ 2 built-in PT100 RTD sensors for monitoring process temperature and high-limit temperature

### Specifications

**Nominal Voltage:** 230 VAC

#### Operating Temperatures:

- Steel IBC: -40 °F to 392 °F (-40 °C to 200 °C)
- Plastic IBC: -40 °F to 158 °F (-40 °C to 70 °C)

**Ambient Temperature Range:** -40 °F to 140 °F (-40 °C to 60 °C)

**Temperature Class:** T6, T5, T4, T3 (depending on temperature control limiter setpoint)


**Zones:** 1/2 (gas); 21/22 (dust)

**Sensor:** 2 standard 3-wire PT100 RTD sensors

**Power Cord:** 10 ft (3 m) long with crimped ferrule terminated leads

**IP Rating:** IP65

### Explosion protection marking

Gas  II 2G Ex e mb IIC T3 Gb

Dust  II 2D Ex e mb IIC T120 °C Db

-40 °C ≤ Ta ≤ +60 °C (ambient temperature)

### EC-type examination certificate


TPS 11 ATEX 29587 011 X



\*Shown with optional cover



**Moisture Resistant**



An ATEX certified temperature controller is required for use with this product

**Part No.: WEXRBL25-230ZESBH**

See page 171 for details

### Ordering Information

Part No. 230 VAC	Capacity gal (l)	Wattage	A Width in (mm)	C Total Length in (mm)	C Heated Length in (mm)
WEXHCIBC-230ZE100-0440XT3	275 (1000)	2400	39.4 (1000)	173.2 (4400)	153.5 (3900)

### Accessories

Part No.	Description
WEXHIIBC	IBC tote tank cover minimizes heat loss and improves efficiency

**Custom Sizes and Designs Available: Contact BriskHeat® or your local distributor for more information.**