FGH/SXH HIGH-TEMPERATURE HEATING BLANKETS

Features & Benefits

- Great for dry-area applications that require temperatures up to 1100°F (593°C)
- Energy-efficient heating element with 1 in (25.4 mm) layer of high-density fiberglass insulation
- Abrasion-resistant fiberglass cloth (FGH) or Samox[®] cloth (SXH)
- Flexible up to 1 in (25.4 mm) bend radius
- Excellent temperature uniformity

Specifications

Exposure Temperature:

- FGH series: 800°F (427°C)

- SXH series: 1100°F (593°C)

Power Density:

- FGH series: 7 W/in² (1.1 W/cm²)

- SXH series: 13 W/in² (2.0 W/cm²)

Voltage: 120 or 240 VAC


Dielectric Strength: Over 2000 volts

Nominal Thickness: 1 in (25.4 mm)

Power Cord: 6 ft (1.8 m) long fiberglass power cord with choice of power plug. See page 180 for choices.



Ordering Information



See page 180 for choices



Custom sizes and designs available: Contact BriskHeat[®] or your local distributor for more information.

Standard Sizes and Wattage

FGH series			SXH series	
Width in (mm)	Length in (mm)	Total Watts	Width in (mm)	Length in (mm)
6 (152)	6 (152)	255	6 (152)	6 (152)
6 (152)	12 (305)	504	6 (152)	12 (305)
6 (152)	24 (610)	1008	6 (152)	24 (610)
8 (203)	8 (203)	448	8 (203)	8 (203)
10 (254)	10 (254)	700	10 (254)	10 (254)
12 (305)	12 (305)	1008	12 (305)	12 (305)
12 (305)	24 (610)	2016	12 (305)	24 (610)
16 (406)	16 (406)	1792	16 (406)	16 (406)
18 (457)	18 (457)	2268	18 (457)	18 (457)
24 (610)	24 (610)	4032*		

* Not available in 120 VAC due to high amperage requirements.

IMPORTANT: Temperature controller is required for this product. See options starting on page 145.

We use BriskHeat silicone rubber heating blankets in a variety of custom sizes to heat several of our production wax tanks. They are easily installed, easily maintained, and last a reasonably long time.

~ Keith Weller Site Supervisor with Desert Whale Jojoba/Lip Chemicals

800-848-7673 | 614-294-3376 | BriskHeat.com | bhtsales1@briskheat.com