

SILICONE RUBBER DRUM/PAIL HEATERS

Features & Benefits

- ▶ Economical 3.6 in (91 mm) wide drum heater
- ▶ Adjustable thermostat — Temperatures up to 425°F (218°C)
- ▶ Designed for metal drums and pails
- ▶ Moisture and chemical resistant — IP 54 rated
- ▶ 6 ft (1.8 m) long power cord with choice of plug or leads

**ECONOMICAL
CHOICE**



**Moisture
& Chemical
Resistant**



Plug & Play



Specifications

Heater Width: 3.6 in (91 mm)

Voltage Options: 120 VAC or 240 VAC

Exposure Temperature: -60°F to 450°F (-51°C to 232°C)

Dielectric Strength: Over 2000 volts

Attachment Type: Expandable spring closure — expands up to 3 in (76 mm)

Silicone Rubber Density: 46.0 oz/yd² (1560 g/m²)

Power Cord: 6 ft (1.8 m) long with

120 VAC: 3-prong grounded plug (NEMA 5-15P)

240 VAC: bare wire leads

IP Rating: IP54



When ordered with
bare wire leads



Up to 392°F
(200°C)

NOTE: If precise temperature control is required for your application, please contact BriskHeat or your local distributor for application assistance and product solutions.

Ordering Information

120 VAC	Part No. 240 VAC	Drum Size gal (l)	Drum Diameter in	Drum Diameter mm	Heater Length in (mm)	Drum Type	Watts
ECON05-1	ECON05-2	3.5 to 7 (13 to 26)	11.1 to 12.1	282 to 307	35.0 (889)	Metal	300
ECON015-1	ECON015-2	15 to 16 (57 to 61)	14.0 to 15.0	355 to 381	44.0 (1118)	Metal	500
ECON030-1	ECON030-2	30 (114)	18.6 to 19.6	472 to 498	58.5 (1486)	Metal	750
ECON055-1	ECON055-2	55 (200 to 208)	22.3 to 23.2	566 to 589	70.0 (1778)	Metal	1100

Accessories

Part No.	Description	
10180	Replacement spring for BriskHeat® Silicone Rubber Drum Heaters	