

SILICONE RUBBER DRUM/PAIL WARMERS

Features & Benefits

- ▶ Preset 85°F (29°C) built-in thermostat
- ▶ Designed for metal and poly drums/pails
- ▶ Moisture and chemical resistant — IP54 rated
- ▶ 6 ft (1.8 m) long power cord with NEMA 5-15P plug
- ▶ Temperature ideal for freeze protection and viscosity control — Maintains temperature between 67°F and 85°F (19°C to 29°C)
- ▶ Safe for both metal and poly drums
- ▶ Suitable for outdoor use
- ▶ Easy-to-use — simple plug-and-play design
- ▶ Rugged — provides long service life and can be used in a wide variety of environments

Specifications

Heater Width: 4 in (102 mm)

Voltage: 120 VAC (other voltages available upon request)

Exposure Temperature: -60°F to 450°F (-51°C to 232°C)

Dielectric Strength: Over 2000 volts

Attachment Type: Expandable spring closure — expands up to 3 in (76 mm)

Silicone Rubber Density: 46.0 oz/yd² (1560 g/m²)

Power Cord: 6 ft (1.8 m) long with standard 120 VAC: 3-prong grounded plug (NEMA 5-15P)

IP Rating: IP54

**With
Preset
Thermostat**



**Moisture
& Chemical
Resistant**



Plug & Play



When ordered with
bare wire leads



Ordering Information

Part No. 120 VAC	Drum Size gal (l)	Drum Diameter in	Drum Diameter mm	Heater Length in (mm)	Drum Type	Pre-set Thermostat	Watt Density	Watts
DHCS10R	3.5 to 7 (13 to 26)	11.1 to 12.1	282 to 307	35.0 (889)				550
DHCS11R	15 to 16 (57 to 61)	14.0 to 15.0	355 to 381	44.0 (1118)	Metal or Poly	85°F (29°C)	5.0 W/in ² (0.78 W/cm ²)	700
DHCS13R	30 (114)	18.6 to 19.6	472 to 498	58.5 (1486)				1000
DHCS15R	55 (200 - 208)	22.3 to 23.2	566 to 589	70.0 (1778)				1200

For 240 VAC models, contact BriskHeat for assistance

Accessories:

Part No.	Description
10180	Replacement spring for BriskHeat® Silicone Rubber Drum Heaters

Heaters should always be placed below fill level of container.