

## SILICONE RUBBER DRUM/PAIL WARMERS

### Features & Benefits

- ▶ Preset 85°F (29°C) built-in thermostat
- ▶ Designed for metal and poly drums/pails
- ▶ Moisture and chemical resistant — IP54 rated
- ▶ 6 ft (1.8 m) long power cord with NEMA 5-15P plug
- ▶ Temperature ideal for freeze protection and viscosity control — Maintains temperature between 67°F and 85°F (19°C to 29°C)
- ▶ Safe for both metal and poly drums
- ▶ Suitable for outdoor use
- ▶ Easy-to-use — simple plug-and-play design
- ▶ Rugged — provides long service life and can be used in a wide variety of environments

### Specifications

**Heater Width:** 4 in (102 mm)

**Voltage:** 120 VAC (other voltages available upon request)

**Exposure Temperature:** -60°F to 450°F (-51°C to 232°C)

**Dielectric Strength:** Over 2000 volts

**Attachment Type:** Expandable spring closure — expands up to 3 in (76 mm)

**Silicone Rubber Density:** 46.0 oz/yd<sup>2</sup> (1560 g/m<sup>2</sup>)

**Power Cord:** 6 ft (1.8 m) long with standard 120 VAC: 3-prong grounded plug (NEMA 5-15P)

**IP Rating:** IP54

**With  
Preset  
Thermostat**



**Moisture  
& Chemical  
Resistant**



**Plug & Play**



When ordered with  
bare wire leads



### Ordering Information

Part No. 120 VAC	Drum Size gal (l)	Drum Diameter in	Drum Diameter mm	Heater Length in (mm)	Drum Type	Pre-set Thermostat	Watt Density	Watts
DHCS10R	3.5 to 7 (13 to 26)	11.1 to 12.1	282 to 307	35.0 (889)				550
DHCS11R	15 to 16 (57 to 61)	14.0 to 15.0	355 to 381	44.0 (1118)	Metal or Poly	85°F (29°C)	5.0 W/in <sup>2</sup> (0.78 W/cm <sup>2</sup> )	700
DHCS13R	30 (114)	18.6 to 19.6	472 to 498	58.5 (1486)				1000
DHCS15R	55 (200 - 208)	22.3 to 23.2	566 to 589	70.0 (1778)				1200

For 240 VAC models, contact BriskHeat for assistance

### Accessories:

Part No.	Description
10180	Replacement spring for BriskHeat® Silicone Rubber Drum Heaters

**Heaters should always be placed below fill level of container.**