

HOTBELT™ WRAPAROUND REFRIGERANT JUG WARMER

Features & Benefits

- ▶ Adjustable fit design with hook & loop strap fits common size cylinders: 30 lb, 50 lb, and 125 lb (13 kg, 23 kg, and 57 kg)
- ▶ Designed to heat the tank surface to 120°F (49°C)
- ▶ Moisture and chemical resistant — IP56 rated
- ▶ 6 ft (1.8 m) long power cord with choice of plug
- ▶ Preheats and keeps refrigerant jug cylinders warm when servicing HVACR systems in cold weather
- ▶ Ensures adequate pressure from refrigerant to A/C or refrigeration system during cold weather servicing
Ideal for portable and outdoor use
- ▶ Easy-to-use — simple plug-and-play design
- ▶ Rugged — provides long service life and can be used in a wide variety of environments

Specifications

Heater Width: 6 in (152 mm)

Length: 26 in (660 mm)

Thermostat: Thermostat is preset to 158°F (70°C) and the heater is designed to heat the surface of the tank to 120°F (49°C)

Exposure Temperature: -60°F to 450°F (-51°C to 232°C)

Voltage: 120, 230, or 240 VAC

Power Density: 1.4 W/in² (0.2 W/cm²)

Dielectric Strength: Over 2000 volts

Silicone Rubber Density: 46.0 oz/yd² (1560 g/m²)

Closure Method: Adjustable strap

Cylinder Diameter Range: Minimum 9 in (229 mm)

Power Cord: 6 ft (1.8 m) long with choice of power plug

IP Rating: IP56

*Variations in ambient temperature and material contents within the cylinder may affect actual surface temperature of the cylinder.

Ordering Information

Part No.	Voltage VAC	Plug Type	Total Watts
HB1001	120	NEMA 5-15P	200
HB2001	240	NEMA 6-15P	200
HB2002	230	CEE 7/7	200

NEW!



Plug & Play



**Moisture
& Chemical
Resistant**



Safe to use with common refrigerants:

- R-410A
- R-407C
- R-139A
- R-22
- R-404
- And more