

## WET-AREA WRAPAROUND TOTE TANK/IBC HEATERS & INSULATORS

### Features & Benefits

- ▶ Extra-durable, water resistant design for outdoor/indoor use and in wash-down environments
- ▶ Insulated, full-coverage design
- ▶ Heater has easy-to-program digital controller: Adjustable up to 140° F (60° C)
- ▶ Lightweight and easy-to-install with adjustable buckles
- ▶ Suitable for both metal and plastic IBC/tote tanks
- ▶ Ideal for a wide range of environments including outdoor and wash-down locations
- ▶ Even heat distribution and maximum energy efficiency
- ▶ Does not contaminate or scorch your product
- ▶ Easy-to-use — simple plug-and-play design
- ▶ Reusable and rugged — long service life
- ▶ Safe — heater has unique 360° grounded heating element and cool-touch surface for your safety

**NEW!**



All-in-one heater with plug-and-play solution

Image above shown with optional top cover (sold separately)



Insulator — Pairs nicely with BriskHeat® Tote Tank/IBC Immersion Heater. See page 139 for details.

Image above shown with optional top cover (sold separately)




Plug & Play



Moisture Resistant



Easy-to-program digital controller



Adjustable nylon straps with buckles

## WET-AREA WRAPAROUND TOTE TANK/IBC HEATERS & INSULATORS

### Specifications

**Outer Material:** Extra-durable polyester cloth  
**Insulation:** 0.5 in (13 mm) thick closed-cell melamine  
**Closure Method:** Adjustable straps with buckles  
**Maximum Exposure Temperature:** 180°F (82°C)  
**Height:** 36 in (914 mm), 42 in (1067 mm), or 48 in (1220 mm)  
**Circumference:** Fits any vessel from 160 in (4064 mm) to 192 in (4877 mm)  
**IP Rating:** IP54

### Additional specifications for heater

**Operating Temperature:** Up to 140°F (60°C)  
**Digital Control:** Programmable in °F and °C  
**Built-in High-Limit Safety Thermostat:** 185°F (85°C)  
**Heating Element:** 360° grounded heating element for your safety  
**Dielectric Strength:** Over 2000 volts  
**Power Cord:** 6 ft (1.8 m) long  
 120 VAC: 3-prong grounded plug (NEMA 5-15P)  
 240 VAC: 3-prong grounded plug (NEMA 6-15P)



Heater  
(TOTEW series)

Insulator  
(TOTEWI series)



Optional Insulating Cover



Certified to UL safety standards  
 Approval is for heater

### Ordering Information

#### Heaters

Part No. 120VAC	Part No. 240VAC	Height in (mm)	Capacity gal (l)	Tank Perimeter Minimum in (mm)	Tank Perimeter Maximum in (mm)	Weight lbs (kg)	Total Wattage
TOTEW361-ADJV	TOTEW362-ADJV	36 (914)	175 - 250 (640 - 950)	160 (4060)	192 (4880)	19 (9)	1440
TOTEW421-ADJV	TOTEW422-ADJV	42 (1067)	275 (1000)	160 (4060)	192 (4880)	23 (10)	1440
TOTEW481-ADJV	TOTEW482-ADJV	48 (1220)	330 (1250)	160 (4060)	192 (4880)	26 (12)	1440

#### Insulators

Part No.	Height in (mm)	Capacity gal (l)	Tank Perimeter Minimum in (mm)	Tank Perimeter Maximum in (mm)	Weight lbs (kg)
TOTEW36IV	36 (914)	175 - 250 (640 - 950)	160 (4060)	192 (4880)	16 (7)
TOTEW42IV	42 (1067)	275 (1000)	160 (4060)	192 (4880)	20 (9)
TOTEW48IV	48 (1220)	330 (1250)	160 (4060)	192 (4880)	23 (11)

#### Accessories

Description	Part No.
Optional insulated top cover	TOTEW-TOPV

Dimensions of top cover: 40 x 40 in (1016 x 1016 mm) with 4 in (102 mm) wide flaps. Flaps expand maximum dimensions to 48 x 48 in (1219 x 1219 mm)

Insulation thickness of top cover: 0.25 in (6 mm)